

CHEWING GUM REMOVER

1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND OF THE COMPANY /UNDERTAKING

Product Name: Chewing Gum Remover

Supplier: Gems Hygiene Supplies
The Business Centre
79 Leigh Street
Sheffield
S9 2PR

Tel: 0114 261 8187
Fax: 0114 261 1489
E: info@ghdirect.co.uk

2. HAZARDS IDENTIFICATION

MAIN HAZARDS Flammable. Irritating to skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

OTHER HAZARDS In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
LOW BOILING POINT HYDROGEN TREATED NAPHTHA-NAPHTHA (PETROLEUM) HYDROTREATED HEAVY	265-150-3	64742-48-9	30-50%	(-) R10; (Xn); (-) R66
LIMONENE (CITRUS DULCIS)	232-433-8	8028-48-6	1-10%	(-)R10, (Xn)R65 (Xi) R38[Sens] R43:
DISTILLATES (PETROLEUM) HYDROTREATED HEAVY			50-70%	

4. FIRST AID MEASURES

INHALATION There may be irritation of the throat with a feeling of tightness in the chest. Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

INGESTION There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting. Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor

SKIN CONTACT There may be irritation and redness at the site of contact. Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

EYE CONTACT There may be irritation and redness. The eyes may water profusely. Bathe the eye with running water for 15minutes. Consult a doctor.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

EXPOSURE HAZARDS Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

PROTECTION OF FIRE-FIGHTERS Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

ENVIRONMENTAL PRECAUTIONS Do not discharge into drains or rivers. Contain the spillage using bunding.

CLEAN-UP PROCEDURES Absorb into dry earth or sand, Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

HANDLING REQUIREMENTS Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

STORAGE CONDITIONS Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

RESPIRATORY EQUIPMENT Self-contained breathing apparatus must be available in case of emergency.

HAND PROTECTION Gloves (solvent-resistant). Viton gloves.

EYE PROTECTION Safety glasses. Ensure eye bath is to hand.

SKIN PROTECTION Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE Liquid

COLOUR Colourless

ODOUR Characteristic odour

EVAPOURATION RATE Moderate

OXIDISING Non-oxidising (by EC criteria)

SOLUBILITY IN WATER Insoluble

ALSO SOLUBLE IN Most organic solvents

VISCOCITY Non-viscous

FLASH POINT°C 24-55

RELATIVE DEINSTEY 0.8 – 0.9 @ 20°C

pH- VALUE, CONC. SOULTION non-aqueous

VOC g/l 800

10. STABILITY AND REACTIVITY

STABILITY Stable under normal conditions. Stable at room temperature.

CONDITIONS TO AVOID Heat. Hot surfaces. Sources of ignition. Flames.

MATERIALS TO AVOID Strong oxidising agents. Strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS In combustion emits toxic fumes.

11. TOXOLOGICAL INFORMATION

ROUTES OF EXPOSURE Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

MOBILITY Readily absorbed into soil.

PERSISTENCE AND DEGRADABILITY Biodegradable

BIOACCUMULATIVE POTENTIAL No bioaccumulation potential.

13. DISPOSAL CONSIDERATIONS

DISPOSAL OF PACKAGING Dispose of as normal industrial waste.

N.B. The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR UN NO. 1993

ADR PACKAGING GROUP III

ADR CLASS NO. 3

ADR CLASSIFICATION CODE F1

ADR SHIPPING NAME FLAMMABLE LIQUID, NOS (DISTILLATES (PETROLEUM) HYDROTREATED HEAVY)

ADR LABELLING	3
ADR HAZARD ID NO.	30
IMDG UN NO	1993
IMDG PACKAGING GROUP	III
IMDG MARINE POLLUTANT	-
IMDG LABELLING	3
IMDG CLASS	3
IMDG EmS	F-E,S-E
IATA UN NO.	1993
IATA PACKAGING GROUP	III
IATA PACKAGING INSTRUCTIONS	309(P&CA); 310(PAO)
IATA LABELLING	3
IATA CLASS	3

15. REGULATORY INFORMATION



LABELLING

RISK PHRASES

SAFETY PHRASES

SEVESO II GUIDELINE

WATER HAZARD CLASS

AIR EMISSION DIRECTIVE

NOTE

HARMFUL

R10 Flammable

R38 Irritating to skin

R43 May cause sensitisation by skin contact

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

S24 Avoid contact with skin.

S37 Wear suitable gloves.

S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

No

1 Classification by VwVwS

Class: III Item no: 5.2.5 Amount m%:100

The regulatory information given above only indicates the principal specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

OTHER INFORMATION

6 X 500ML; NOT SUBJECT TO ADR

2 X 5LTR ; NOT SUBJECT TO ADR

RISK PHRASES USED IN S3

R10 Flammable

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R38 Irritating to skin.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

LEGAL DISCLAIMER

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.