

# ONE SHOT CITRUS

## 1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND OF THE COMPANY /UNDERTAKING

Product Name: ONE SHOT CITRUS

Supplier: Gems Hygiene Supplies  
The Business Centre  
79 Leigh Street  
Sheffield  
S9 2PR

Tel: 0114 261 8187  
Fax: 0114 261 1489  
E: info@ghdirect.co.uk

## 2. HAZARDS IDENTIFICATION

R12 Extremely flammable.

PRESSURISED CONTAINER- increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification F+R12 R52/53.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+R12
d-LIMONENE	227-813-5	5989-27-5	0.5-1%	R10 R43 Xi;R38 N;R50/53
PROPANE	200-827-9	74-98-6	30-60%	F+R12

The Full text for all R-Phrases are displayed in Section 16

## 4. FIRST AID MEASURES

INHALATION	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.
INGESTION	Rinse mouth thoroughly. Get medical attention if discomfort continues.
SKIN CONTACT	wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

## 5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA	Use powder, dry chemicals, sand, dolomite etc. Water spray fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSION HAZARDS	Aerosol cans may explode in a fire.

## 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses.

## 7. HANDLING AND STORAGE

USAGE PRECAUTIONS	Keep away from heat, sparks and open flame, avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
USAGE DESCRIPTION	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

NAME	STD	TWA-8hrs	STEL -15 min	NOTES
BUTANE	WEL	600ppm	1450mg/m3 750ppm	1810mg/m3

ENGINEERING MEASURES Provide adequate general and local exhaust ventilation.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
COLOUR	Colourless
ODOUR	characteristic, citrus
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DENSITY	0.55 @ 20°C
FLASH POINT (°C)	-74 N/A
AUTO IGNITION TEMPERATURE	+405
FLAMMABILITY LIMIT - LOWER%	1.8
FLAMMABILITY LIMIT - UPPER%	10.0

## 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates. Toxic gases/vapours/fumes of Carbon monoxide (CO) Carbon Dioxide (CO <sub>2</sub> )

## 11. TOXOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT	No specific health warning noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

## 12. ECOLOGICAL INFORMATION

ECOTOXICITY	Harmful to aquatic organisms, Because product is so volatile if it is released into the environment the liquid would very quickly turn into vapour.
-------------	---

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
------------------	---

## 14. TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	2
ADR CLASS NO	2 Class Code 5F Label: 2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

## 15. REGULATORY INFORMATION



### LABELLING

Extremely Flammable (F+)

### RISK PHRASES

R12 Extremely flammable. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### SAFETY PHRASES

S16 Keep away from sources of ignition- No smoking. S51 Use in only well ventilated areas. S2 Keep out of reach of children. P14 Contains d-LIMONENE. May produce an allergic reaction.

### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

### APPROVED CODE OF PRACTICE

Classification and labelling of substances and preparations dangerous for supply.

### GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG (108)

## 16. OTHER INFORMATION

### GENERAL INFORMATION

The following risk phrases relate to the raw material in the product and not the product itself  
28/01/2008

### REVISION DATE

### REV. NO. / REPL. SDS GENERATED

4

### RISK PHRASES USED IN FULL

R12 Extremely Flammable. R12 Extremely flammable. R10 Flammable. R38 Irritating to skin. R43 May cause sensitization by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



## ONE SHOT VANILLA

### 1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND OF THE COMPANY /UNDERTAKING

Product Name: ONE SHOT VANILLA

Supplier: Gems Hygiene Supplies  
The Business Centre  
79 Leigh Street  
Sheffield  
S9 2PR

Tel: 0114 261 8187  
Fax: 0114 261 1489  
E: info@ghdirect.co.uk

### 2. HAZARDS IDENTIFICATION

R12 Extremely flammable. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
PRESSURISED CONTAINER- increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification F+R12. R52/53

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
(L) Hexyl Cinnamyl	202-983-3	101-86-0	<1%	R43
1- (Hexahydrotetramethanoazulenyl) ethan-1-one	251-020-3	32388-55-9	<1%	N;R50/53
PROPANE	203-448-7	106-97-8	30-60%	F+R12
Glaxolide	214-946-9	1222-05-5	<1%	N;R50/53

The Full text for all R-Phrases are displayed in Section 16

#### 4. FIRST AID MEASURES

INHALATION	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.
INGESTION	Rinse mouth thoroughly. Drink plenty of water. Get medical attention.
SKIN CONTACT	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA SPECIAL FIRE FIGHTING PROCEDURES	Use powder, dry chemicals, sand, dolomite etc. Water spray fog or mist.
UNUSUAL FIRE & EXPLOSION HAZARDS	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Aerosol cans may explode in a fire.

#### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses.

#### 7. HANDLING AND STORAGE

USAGE PRECAUTIONS	Keep away from heat, sparks and open flame, avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
USAGE DESCRIPTION	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

NAME	STD	TWA-8hrs	STEL -15 min	NOTES
BUTANE	WEL	600ppm	1450mg/m <sup>3</sup> 750ppm	1810mg/m <sup>3</sup>

ENGINEERING MEASURES	Provide adequate general and local exhaust ventilation.
----------------------	---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
ODOUR	characteristic, vanilla
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DEINSTRY	0.55 @ 20°C
FLASH POINT (°C)	-74 N/A
AUTO IGNITION TEMPERATURE	+405
FLAMMABILITY LIMIT- LOWER%	1.8
FLAMMABILITY LIMIT –UPPER%	10.0

#### 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates. Toxic gases/vapours/fumes of Carbon monoxide ( Co) Carbon Dioxide (Co <sub>2</sub> )

#### 11. TOXOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT	No specific health warning noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

## 12. ECOLOGICAL INFORMATION

ECOTOXICITY	Not regarded as dangerous for the environment.
-------------	--

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
------------------	---

## 14. TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	2
ADR CLASS NO	2 Class Code 5F Label: 2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

## 15. REGULATORY INFORMATION

### LABELLING



### RISK PHRASES

Extremely Flammable (F+)

### SAFETY PHRASES

R12 Extremely flammable, R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### STATUTORY INSTRUMENTS

S9 Keep container in a well-ventilated place. S16 Keep away from sources of ignition- No smoking. S51 Use in only well ventilated areas. P14 Contains (L) Hexyl Cinnamyl. May produce an allergic reaction. S2 Keep out of reach of children.

### APPROVED CODE OF PRACTICE

Chemicals (Hazard Information and Packaging) Regulations.

### GUIDANCE NOTES

Classification and labelling of substances and preparations dangerous for supply.

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG (108)

## 16. OTHER INFORMATION

### GENERAL INFORMATION

The following risk phrases relate to the raw material in the product and not the product itself

### REVISION DATE

25/01/2008

### REV. NO. / REPL. SDS GENERATED

3

### RISK PHRASES USED IN FULL

R12 Extremely Flammable. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R43 may cause sensitization by skin contact. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# ONE SHOT WILD ORCHID

## 1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND OF THE COMPANY /UNDERTAKING

Product Name: ONE SHOT WILD ORCHID	Supplier: Gems Hygiene Supplies The Business Centre 79 Leigh Street Sheffield S9 2PR	Tel: 0114 261 8187 Fax: 0114 261 1489 E: info@ghdirect.co.uk
------------------------------------	--	--

## 2. HAZARDS IDENTIFICATION

R12 Extremely flammable.  
PRESSURISED CONTAINER- increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.  
Classification F+R12

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+R12
PROPANE	200-827-9	74-98-9	30-60%	F+R12

The Full text for all R-Phrases are displayed in Section 16

## 4. FIRST AID MEASURES

INHALATION	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.
INGESTION	Rinse mouth thoroughly. Get medical attention if discomfort continues.
SKIN CONTACT	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYE CONTACT	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

## 5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA SPECIAL FIRE FIGHTING PROCEDURES	Use powder, dry chemicals, sand, dolomite etc. Water spray fog or mist.
UNUSUAL FIRE & EXPLOSION HAZARDS	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Aerosol cans may explode in a fire.

## 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses.

## 7. HANDLING AND STORAGE

USAGE PRECAUTIONS	Keep away from heat, sparks and open flame, avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
USAGE DESCRIPTION	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

NAME	STD	TWA-8hrs	STEL -15 min	NOTES
BUTANE	WEL	600ppm	1450mg/m3 750ppm	1810mg/m3

ENGINEERING MEASURES Provide adequate general and local exhaust ventilation.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
ODOUR	characteristic, floral
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DEINSTRY	0.55 @ 20°C
FLASH POINT (°C)	-74 N/A
AUTO IGNITION TEMPERATURE	+405
FLAMMABILITY LIMIT- LOWER%	1.8
FLAMMABILITY LIMIT -UPPER%	10.0

## 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates. Toxic gases/vapours/fumes of Carbon monoxide ( Co) Carbon Dioxide (Co2)

## 11. TOXOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT	No specific health warning noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

## 12. ECOLOGICAL INFORMATION

ECOTOXICITY	Not regarded as dangerous for the environment.
-------------	--

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
------------------	---

## 14. TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	2
ADR CLASS NO	2 Class Code 5F Label: 2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

## 15. REGULATORY INFORMATION



## LABELLING

### RISK PHRASES

### SAFETY PHRASES

### STATUTORY INSTRUMENTS

### APPROVED CODE OF PRACTICE

### GUIDANCE NOTES

Extremely Flammable (F+)

R35 Causes severe burns.

S16 Keep away from sources of ignition- No smoking. S51 Use in only well ventilated areas.

S2 Keep out of reach of children.

Chemicals (Hazard Information and Packaging) Regulations.

Classification and labelling of substances and preparations dangerous for supply.

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG (108)

## 16. OTHER INFORMATION

### GENERAL INFORMATION

#### REVISION DATE

The following risk phrases relate to the raw material in the product and not the product itself

25/01/2008

#### REV. NO. / REPL. SDS GENERATED

3

#### RISK PHRASES USED IN FULL

R12 Extremely Flammable. R12 Extremely flammable.

# ONE SHOT CRANBERRY

## 1. IDENTIFICATION OF THE SUBSTANCE /PREPARATION AND OF THE COMPANY /UNDERTAKING

Product Name: ONE SHOT CRANBERRY

Supplier: Gems Hygiene Supplies

Tel: 0114 261 8187

The Business Centre

Fax: 0114 261 1489

79 Leigh Street

E: info@ghdirect.co.uk

Sheffield

S9 2PR

## 2. HAZARDS IDENTIFICATION

R12 Extremely flammable.

PRESSURISED CONTAINER- increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

Classification F+R12

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	EINICS No.	CAS No.	Content	Classification
BUTANE	203-448-7	106-97-8	30-60%	F+R12
PROPANE	200-827-9	74-827-9	30-60%	F+R12

The Full text for all R-Phrases are displayed in Section 16

## 4. FIRST AID MEASURES

### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.

### INGESTION

Rinse mouth thoroughly. Get medical attention if discomfort continues.

### SKIN CONTACT

wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

### EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

## 5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA SPECIAL FIRE FIGHTING PROCEDURES	Use powder, dry chemicals, sand, dolomite etc. Water spray fog or mist.
UNUSUAL FIRE & EXPLOSION HAZARDS	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours. Aerosol cans may explode in a fire.

#### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Inform authorities if large amounts are involved.
ENVIRONMENTAL PRECAUTIONS	Any spillage needs to be contained and not allowed to enter water courses.

#### 7. HANDLING AND STORAGE

USAGE PRECAUTIONS	Keep away from heat, sparks and open flame, avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.
USAGE DESCRIPTION	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

NAME	STD	TWA-8hrs	STEL -15 min	NOTES
BUTANE	WEL	600ppm	1450mg/m3 750ppm	1810mg/m3

ENGINEERING MEASURES	Provide adequate general and local exhaust ventilation.
----------------------	---

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
ODOUR	characteristic, cranberry
PHYSICAL DATA COMMENTS	Information given relates to total aerosol container contents.
RELATIVE DEINSTEY	0.55 @ 20°C
FLASH POINT (°C)	-74 N/A
AUTO IGNITION TEMPERATURE	+405
FLAMMABILITY LIMIT- LOWER%	1.8
FLAMMABILITY LIMIT -UPPER%	10.0

#### 10. STABILITY AND REACTIVITY

STABILITY	Stable under normal temperature conditions.
CONDITIONS TO AVOID	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.
HAZARDOUS DECOMPOSITION PRODUCTS	Fire creates. Toxic gases/vapours/fumes of Carbon monoxide ( Co) Carbon Dioxide (Co2)

#### 11. TOXOLOGICAL INFORMATION

INHALATION	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiant). Unconsciousness.
SKIN CONTACT	No specific health warning noted.
EYE CONTACT	Irritation of eyes and mucous membranes.

#### 12. ECOLOGICAL INFORMATION

ECOTOXICITY	Not regarded as dangerous for the environment.
-------------	--

#### 13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
------------------	---

#### 14. TRANSPORT INFORMATION

UN NO. ROAD	1950
UK ROAD CLASS	2

ADR CLASS NO	2 Class Code 5F Label: 2.1
PROPER SHIPPING NAME	AEROSOLS, FLAMMABLE
UN NO. SEA	1950
IMDG CLASS	2.1
IMDG PACK GR	N/A
UN NO. AIR	1950
AIR CLASS	2.1
AIR PACK GR.	N/A

#### 15. REGULATORY INFORMATION



#### LABELLING

#### RISK PHRASES

#### SAFETY PHRASES

#### STATUTORY INSTRUMENTS

#### APPROVED CODE OF PRACTICE

#### GUIDANCE NOTES

Extremely Flammable (F+)

R12 Extremely Flammable.

S16 Keep away from sources of ignition- No smoking. S51 Use in only well ventilated areas.

S2 Keep out of reach of children.

Chemicals (Hazard Information and Packaging) Regulations.

Classification and labelling of substances and preparations dangerous for supply.

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG (108)

#### 16. OTHER INFORMATION

#### GENERAL INFORMATION

#### REVISION DATE

#### REV. NO. / REPL. SDS GENERATED

#### RISK PHRASES USED IN FULL

The following risk phrases relate to the raw material in the product and not the product itself

25/01/2008

3

R12 Extremely Flammable. R12 Extremely flammable.